

Tabella delle dimensioni

DIN / ISO	GAS / ASA (pollici)	Diametro esterno x spessore (mm)	Raggio curvatura (mm)	Tolleranze sul raggio (mm)
15	1/2	21.3x1.5	31.8	± 2.5
15	1/2	21.3x2.0	31.8	± 2.5
20	3/4	26.9x1.5	28.5	± 2.5
20	3/4	26.9x2.0	28.5	± 2.5
25	1	33.7x1.5	38.1	± 2.5
25	1	33.7x2.0	38.1	± 2.5
25	1	33.7x2.5	38.1	± 2.5
32	1 1/4	42.4x1.5	47.5	± 2.5
32	1 1/4	42.4x2.0	47.5	± 2.5
32	1 1/4	42.4x2.5	47.5	± 2.5
40	1 1/2	48.3x1.5	57.2	± 3.0
40	1 1/2	48.3x2.0	57.2	± 3.0
40	1 1/2	48.3x2.5	57.2	± 3.0
50	2	60.3x1.5	76.2	± 3.0
50	2	60.3x2.0	76.2	± 3.0
50	2	60.3x2.5	76.2	± 3.0
50	2	60.3x3.0	76.2	± 3.0
65	2 1/2	76.1x2.0	95.2	± 3.0
65	2 1/2	76.1x2.5	95.2	± 3.0
65	2 1/2	76.1x3.0	95.2	± 3.0
80	3	88.9x2.0	114.3	± 3.0
80	3	88.9x2.5	114.3	± 3.0
80	3	88.9x3.0	114.3	± 3.0
90	3 1/2	101.6x2.0	133.3	± 3.0
90	3 1/2	101.6x3.0	133.3	± 3.0
100	4	114.3x2.0	152.4	± 3.0
100	4	114.3x2.5	152.4	± 3.0
100	4	114.3x3.0	152.4	± 3.0
125	5	139.7x2.0	190.5	± 4.0
125	5	139.7x3.0	190.5	± 4.0
125	5	139.7x4.0	190.5	± 4.0
125	5	141.3x2.0	190.5	± 4.0
125	5	141.3x2.5	190.5	± 4.0
125	5	141.3x3.0	190.5	± 4.0
125	5	141.3x4.0	190.5	± 4.0
150	6	168.3x2.0	228.5	± 4.0
150	6	168.3x2.5	228.5	± 4.0
150	6	168.3x3.0	228.5	± 4.0
150	6	168.3x4.0	228.5	± 4.0
200	8	219.1x2.5	305.0	± 4.0
200	8	219.1x3.0	305.0	± 4.0
200	8	219.1x4.0	305.0	± 4.0
250	10	273.0x2.5	381.0	± 5.0
250	10	273.0x3.0	381.0	± 5.0
250	10	273.0x4.0	381.0	± 5.0
300	12	323.9x2.5	457.2	± 5.0
300	12	323.9x3.0	457.2	± 5.0
300	12	323.9x4.0	457.2	± 5.0
350	14	355.6x3.0	534.0	± 5.0
350	14	355.6x4.0	534.0	± 5.0
350	14	355.6x5.0	534.0	± 5.0
400	16	406.4x3.0	609.0	± 5.0
400	16	406.4x4.0	609.0	± 5.0
400	16	406.4x5.0	609.0	± 5.0
450	18	457.2x3.0	609.0	± 5.0
450	18	457.2x4.0	609.0	± 5.0
450	18	457.2x5.0	609.0	± 5.0
500	20	508.0x4.0	762.0	± 5.0
500	20	508.0x5.0	762.0	± 5.0
500	20	508.0x6.0	762.0	± 5.0

Acciaio Inox  
Aisi 304-304L  
316-316L

R = 1.5 Ø  
Acciaio inox  
Aisi 304 / 304L  
316-316L

